# HandiLaz® Mini II

Handheld Airborne Particle Counter

Complete Troubleshooting Solution
0.2 µm to 10 µm sensitivity
Lightweight
Easy to use

Without measurement there is no control

The HandiLaz® Mini II particle counter is ergonomically designed to fit in the palm of your hand. Rugged and dependable, the Mini II provides tremendous value for cost-conscious users who want a reliable, easy-to-use, handheld particle counter.

This product is ideal for users who are in need of convenient cleanroom monitoring after initial construction, operations monitoring and as a diagnostic tool to troubleshoot sources of particle generation without the hassle of heavy equipment and support overhead.

# Complete Accessory Kit Included





# **BENEFITS**

#### **Cost Effective**

• Low-cost alternative for spot monitoring and troubleshooting

Handilaz® Mini II

- Versatile for many applications
- Rechargeable battery with minimal downtime

# Convenient, Easy-to-Use

- Particle measurements in seconds
- Simple, intuitive user interface
- USB and SD storage of data

# **Compact and Portable**

- 3.2 in (81 mm) wide
- Weighs only 1.8 lb (0.83 kg)
- User-replaceable Li-lon rechargeable battery for 5-hour continuous counting

# **FEATURES**

- 200 nm to 10  $\mu m$  size range, suitable for Semiconductor, Advanced Processing and Pharmaceutical applications
- Internal pulse height analyzer allows for unlimited selection of channel sizes
- 10 nm resolution
- Integration of temperature and differential pressure into particle measurement
- Calibrated to ISO 21501-4 Standard
- Simple touchscreen and single button operation
- Advanced on-screen analysis

# **APPLICATIONS**

- Conducting ISO 3 to 9 certification of cleanrooms
- Point-of-use measurements in cleanrooms
- Detecting local particle sources
- Filter testing and leak detection
- Portable particle counting
- 0.2 micron sensitivity allows for effective particle detection for semiconductor equipment and component manufacturers

# HandiLaz® Mini II

# Handheld Airborne Particle Counter

Specifications

Size Range	0.2 μm (50%) to 10 μm (continuous)
Size Channels	Fully user-selectable size channels. Capture size information for each and every single particle.
Flow Rate	0.1 CFM (2.83 LPM), with internal flow meter (1% FS) and active flow control
Pressure	115 kPa max, 1 Pa noise-free resolution
Laser Source	High power, > 10,000 hour laser diode with active control. Temperature compensated and stabilized.
Battery	User-replaceable Li-lon, 5 hour continuous counting, 10 hour intermittent counting
Data Storage	External SD card and external memory
Connection	USB, SD card
Display	3.5 inch Color LCD
Dimensions (H x W x L)	3.2 x 5.4 x 1.7 in (8.2 x 13.7 x 4.2 cm)
Weight	1.8 lb (0.83 kg)
Supported Standards	ISO 21501-4 (instrument), US FED STD 209E and ISO 14644-1:2015 (cleanroom classification)
TRH Sensor	Temperature: $0 - 50 ^{\circ}\text{C} \pm 0.1 ^{\circ}\text{C}$ , internal sensor for flow and $0 - 50 ^{\circ}\text{C} \pm 0.5 ^{\circ}\text{C}$ , external sensor for ambient Humidity: $5 - 95\% \pm 2\%$ external sensor
Environment	15 - 35 °C (ambient temperature)

#### **HEADQUARTERS**

5475 Airport Blvd Boulder, Colorado 80301 USA T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support T: +1 800 557 6363

Customer Response Center T: +1 877 475 3317 E: info@pmeasuring.com

www.pmeasuring.com info@pmeasuring.com



#### **GLOBAL OFFICES**

#### AUSTRIA

T: +43 512 390 500

E: pmsaustria@pmeasuring.com

#### BENELUX

T: +32 10 23 71 56

E: pmsbelgium@pmeasuring.com

# BRAZIL

T: +55 11 5188 8227

E: pmsbrazil@pmeasuring.com

#### CHINA

T: +86 21 6113 3600

E: pmschina@pmeasuring.com

# FRANCE

T: 33(0)1 60 10 32 96

E: pmsfrance@pmeasuring.com

#### GERMANY

T: +49 6151 6671 632

E: pmsgermany@pmeasuring.com

## ITALY

T: +39 06 9053 0130

E: pmssrl@pmeasuring.com

#### **JAPAN**

T: +81 3 5298 8175

E: pmsjapan@pmeasuring.com

#### KORFA

T: +82 31 286 5790

E: pmskorea@pmeasuring.com

#### MEXICO

T: +52 55 2271 5106

E: pmsmexico@pmeasuring.com

#### ORDIC

T: +45 707 028 55

E: pmsnordic@pmeasuring.com

## PUERTO RICO

T: +1 787 718 9096

E: pmspuertorico@pmeasuring.com

#### SINGAPORE

T: +65 6496 0330

E: pmssingapore@pmeasuring.com

## SWITZERLAND

T: +41 71 987 01 01

E: pmsswitzerland@pmeasuring.com

# TAIWAN

T: 886-3-5525300 Ext: 301

E: pmstaiwan@pmeasuring.com