

Without measurement there is no control®

SLS-20

Syringe Liquid Sampler



For batch sampling applications with Chem 20™ and Chem 20-HI particle counters

The SLS-20 Syringe Liquid Sampler enables Chem 20™ or Chem 20-HI particle counters to operate in batch sampling applications. It is ideal for precise, small-volume sampling.

The system consists of an SLS-20 for either corrosive or non-corrosive liquids, all connections necessary to interface with a compatible Chem 20 or Chem 20-HI particle counter, and optional software.

BENEFITS

- 20 nm sensitivity provides unmatched level of process, chemical and filter monitoring
- Fluoropolymer syringe standard for use with HF
- Minimal chemical volume used
- Fully automated system
- Menu-driven data collection
- Extremely accurate measurements
- Compatible with corrosive and non-corrosive liquids

FEATURES

- With SamplerSight software, includes data generation into pre-formatted report types and spreadsheets
- Internal leak detection
- Repeatable recipes for consistent sampling parameters
- Software for data collection and trending
- Optional password security

APPLICATIONS

- Small volume chemical quality assurance
- Parts cleanliness testing
- Laboratory water sampling
- Industries: semiconductor, pharmaceutical, data storage, medical, aerospace, automotive
- Sampling chemical out of finished product packaging
- Sampling out of wet process tanks for process and filter monitoring

SLS-20 Syringe Liquid Sampler

PARAMETER	SPECIFICATION
Syringe size	50 ml (standard), 25 ml (optional)
Sampling mode	Vacuum, Batch
Wetted surface materials	Kel-F®, PFA, PTFE, Kalrez®
Sample volume	Adjustable with software interface
Sample temperature	59 – 104 °F (15 – 40 °C)
Dimensions (l x w x h)	10.0 x 9.0 x 12.3 in (25.4 x 22.9 x 31.2 cm), not including particle counter
Weight	14 lb (6.4 kg), not including particle counter
Power	100 – 240 V, 50 – 60 Hz
Environment	Temperature: 50 – 86 °F (10 – 30 °C) Humidity: Non-condensing



NEED MORE INFORMATION? Scan the QR code to connect with our team for guidance



HEADQUARTERS

7477 E. Dry Creek Parkway,
Niwot, CO, 80503 USA
T: +1 303 443 7100

Instrument Service & Support

T: +1 303-443-7100 ext.447

Service and Calibration

E: workorders@pmeasuring.com

Technical Support

E: techsupport@pmeasuring.com

Software or System Support

E: ssupport@pmeasuring.com

Customer Service

and Order Processing

E: customerorders@pmeasuring.com

GLOBAL OFFICES

AUSTRIA

T: +43 171 728 285

E: pmsaustria@pmeasuring.com

BELGIUM/BENELUX

T: +32 10 23 71 56

E: pmsbelgium@pmeasuring.com

BRAZIL

T: +55 11 5188 8227

E: pmsbrazil@pmeasuring.com

CHINA

T: +86 400 081 8020

E: pmschina@pmeasuring.com

FRANCE

T: +33 682 991 798

E: pmsfrance@pmeasuring.com

GERMANY

T: +49 351 8896 3850

E: pmsgermany@pmeasuring.com

IRELAND

T: +353 1 295 7373

E: Info.ie@pmeasuring.com

ITALY

T: +39 06 9053 0130

E: pmsrli@pmeasuring.com

JAPAN

T: +81 44 589 3498

E: pmsjapan@pmeasuring.com

KOREA

T: +82 31 286 5790

E: pmskorea@pmeasuring.com

NORDIC

T: +45 7070 2855

E: pmsnordic@pmeasuring.com

PUERTO RICO

T: +1 786 564 3356

E: pmspuertorico@pmeasuring.com

SINGAPORE

T: +65 6496 0342

E: pmssingapore@pmeasuring.com

SWITZERLAND

T: +41 71 987 01 01

E: pmsswitzerland@pmeasuring.com

TAIWAN

T: 886-3-5525300

E: pmstaiwan@pmeasuring.com

UNITED KINGDOM

T: +44 (0)1733 454 207

E: Info.uk@pmeasuring.com



Chem 20™ are registered trademarks of Particle Measuring Systems, Inc.
All other trademarks are the property of their respective owners.
Particle Measuring Systems, Inc. reserves the right to change specifications
without notice. © 2026 Particle Measuring Systems, Inc. All rights reserved.
06162026