

LiQuilaz[®] II E Series

Particle Counting Spectrometer for Liquids



The LiQuilaz[®] II E series optical particle counters are volumetric particle counters with sizing sensitivities from 1.5 – 125 μm .

LiQuilaz II sensors provide the same levels of accuracy, reliability and repeatability that customers have trusted for many years. LiQuilaz II sensors feature both RS-485 and Ethernet network communications. The new Ethernet capability increases product flexibility and makes installation significantly easier.

Volumetric particle counters offer the highest precision possible by measuring 100% sample volumes so that short sampling intervals can be utilized without sacrificing statistical significance.

BENEFITS

Yield Improvement

- Real-time characterization and analysis of particle concentration for immediate response to contamination
- Optional software makes process control easy by providing alarm settings, status conditions, sampler setup, and online help
- Volumetric measurements provide greater accuracy for tighter process control

Versatile

- Supports a wide range of applications and fluids
- E15P and E20 are available for online use
- E15P and E20P are available for use with syringe samplers
- Online and batch sampling capabilities
- RS-485 and Ethernet networking compatibility
- Ethernet TCP/IP communication
- Supports 21 CFR Part 11 in combination with SamplerSight Pharma software

Easy to Use

- Small footprint for easy placement anywhere in the process
- Flexible software provides numerous viewing options for real-time or retrieved data

FEATURES

- Sizing sensitivities from 1.5 – 125 μm
- 15 user-adjustable sizing channels
- Volumetric: 100% view volume
- Facility Net, SamplerSight, Pharmaceutical Net, or SamplerSight Pharma
- Compact system
- Compatible with 3rd party systems using RS 485 Modbus protocol

APPLICATIONS

- Pharmaceutical WFI, PW performance verification
- Medical device cleanliness testing
- Parenteral sampling
- Detect abrasive particles
- Continual process improvements
- USP 788-1788 compliance with the SLS sampler family



Without measurement there is no control

LiQuilaz[®] II E Series

Particle Counting Spectrometer for Liquids

Specifications

	LiQuilaz II E20P	LiQuilaz II E20	LiQuilaz II E15P
Size range	2 – 125 µm	2 – 125 µm	1.5 – 125 µm
Flow rate	20 ± 10% ml/min	70 ± 10% ml/min	20 ± 10% ml/min
Sample volume	Volumetric 20 ml/min (100%)	Volumetric 70 ml/min (100%)	Volumetric 20 ml/min (100%)
Size channels	User adjustable from 1 to 15		
Resolution	Less than 10% at 10 µm		
Maximum concentration*	10,000 particles/ml		
Sample temperature	50 – 122 °F (0 – 50 °C)		
Zero count	< 50 counts/liter		
Pressure range	0 - 100 psi		
Laser source	Laser diode		
Wetted surface materials	Fused silica, black quartz, Kalrez [®] and Kel-F [®]		
Liquid connections	3 mm flare or 1/4-inch Flaretek [®]		
Dimensions (l, w, h)	12.75 x 4.25 x 4.5 in (32.4 x 10.8 x 11.4 cm)		
Weight	6.1 lb (2.8 kg)		
Electrical rating	100 - 240 V, 50/60 Hz, 0.75 A		
Communication modes	5-wire, RS-485, DE9 connectors, PMS serial communications protocol, 10/100BaseT Ethernet, PMS Ethernet Protocol, Modbus TCP		
Calibration fluid	DI water		
Calibration	Materials used are traceable to U.S. National Institute of Standards and Technology (NIST) and/or Japanese Institute of Standards (JIS)		
Environment	Temperature: 50 – 95 °F (10 – 35 °C); Humidity: non-condensing		

*Greater than 90% accuracy (less than 10% coincidence loss) at maximum recommended concentration.

LiQuilaz[®] is a registered trademark of Particle Measuring Systems, Inc.

Teflon[®] is a registered trademark of The Chemours Company, FC, LLC.

Kalrez[®] is a registered trademark of DuPont.

Kel-F[®] is a registered trademark of 3M.

All other trademarks are the property of their respective owners.

Particle Measuring Systems, Inc. reserves the right to change specifications without notice.

© 2017 Particle Measuring Systems, Inc.

All rights reserved.



**PARTICLE
MEASURING
SYSTEMS[®]**

HEADQUARTERS

5475 Airport Blvd
Boulder, Colorado 80301 USA
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support
T: +1 800 557 6363

Customer Response Center
T: +1 877 475 3317
E: info@pmeasuring.com

GLOBAL OFFICES

AUSTRIA
T: +43 512 390 500
E: pmsaustria@pmeasuring.com

BENELUX
T: +32 10 23 71 56
E: pmsbelgium@pmeasuring.com

BRAZIL
T: +55 11 5188 8227
E: pmsbrazil@pmeasuring.com

CHINA
T: +86 21 6113 3600
E: pmschina@pmeasuring.com

FRANCE
T: +33 (0)6 82 99 17 98
E: pmsfrance@pmeasuring.com

GERMANY
T: +49 6151 6671 632
E: pmsgermany@pmeasuring.com

ITALY
T: +39 06 9053 0130
E: pmsrl@pmeasuring.com

JAPAN
T: +81 3 5298 8175
E: pmsjapan@pmeasuring.com

KOREA
T: +82 31 286 5790
E: pmskorea@pmeasuring.com

MEXICO
T: +52 55 2271 5106
E: pmsmexico@pmeasuring.com

NORDIC
T: +45 707 028 55
E: pmsnordic@pmeasuring.com

PUERTO RICO
T: +1 787 718 9096
E: pmspuertorico@pmeasuring.com

SINGAPORE
T: +65 6496 0330
E: pmsingapore@pmeasuring.com

SWITZERLAND
T: +41 71 987 01 01
E: pmsswitzerland@pmeasuring.com

TAIWAN
T: 886-3-5525300 Ext: 301
E: pmstaiwan@pmeasuring.com